



ZETTEX

STICK WITH US

TECHNICAL DATA SHEET

Flexcryl Exterior

Zettex Europe B.V.
Plaza 20, 4782 SK Moerdijk
The Netherlands
+31 (0)888-93 88 39
info@zettex.com
www.zettex.com

Product description

Zettex Flexcryl Exterior a high-quality sealer which is paintable with almost all types of paint systems and avoid crack and discolouring. Besides that, the Flexcryl Exterior is suitable for outdoor use. Flexcryl Exterior is suitable for the sealing of joints between window frames of wood and metal. He is suitable for joints between walls and stairs and for concrete and ceiling elements.

Material

Acryl

Advantages

- Directly paintable with all types of paint.
- Non crack
- For in and outside use
- Noncorrosive
- Adhere on every surface without use of a primer

Application

Surfaces to be sealed should be clean and dry, free of dust or grease, which could cause a deficient adherence. You can use Zettex Proficleaner to clean the surfaces. Zettex Flexcryl Exterior can be overpainted once it is cured. After using Zettex Flexcryl Exterior, you can clean hands with Zettex Cleaning Wipes.

Packaging

310 ml cartridge

Safety recommendations

Please read our MSDS before using this product.

Storage

Zettex Flexcryl Exterior has a shelf life of 12 months, stored in a dry place at or below +25°C in its original container.

Certificates



Properties	Specifications
Aspect	Acryl
Specific gravity	1.47 g/cm ³
Skimming time	12-20 min
Application temperature	+5 to +35°C
After curing service temperature	-20 to +80°C

Hardness Shore A	17 (ISO 868)
Elongation at break	200 %